

## LED STRIP 7W/M

Part #- 110-3528-140-7 - 110VAC  
 127-3528-140-7 - 127VAC  
 220-3528-140-7 - 220VAC



### Features:

1. Voltage: AC110/127/220V. (No Driver Necessary)
2. LED quantity. 140pcs SMD3528 LED per Meter
3. Power Consumption: 7W/Meter
4. Current: 40mA per Meter
5. Luminous: 770 Lumens per Meter Super Brightness (See Table Below)
6. Can be cut every 50cm (110V/127V) & every 100cm (220V)
7. Dimension: Width –14 mm / Thickness—6mm
8. Package: 5 Meters (16.4 Ft) /reel
9. Beam Angle: 120 Degrees
10. Operating temperature: - 20 Degrees C. to 50 Degrees C. (-4 F to 122 F)
11. Life - 50,000 Hours.
12. Adhesive 3M tape backing.
13. Indoor & Outdoor Use—IP65 Water Resistant.
14. Compatible with Lutron & Leviton LED dimmers. (100% - 50% dimming)

COLOR	DIMENSIONS (mm)	LED / M	VOLTAGE	WATTS / M	LUMENS / M
Red	5000*14*6	140/m	AC110/127/220V	7W	364
Yellow	5000*14*6	140/m	AC110/127/220V	7W	364
Blue	5000*14*6	140/m	AC110/127/220V	7W	112
Green	5000*14*6	140/m	AC110/127/220V	7W	575
White (5700K)	5000*14*6	140/m	AC110/127/220V	7W	810
Warm White (2700K)	5000*14*6	140/m	AC110/127/220V	7W	770

## LED STRIP 7W/M

Part #- 110-3528-140-7 - 110VAC  
127-3528-140-7 - 127VAC  
220-3528-140-7 - 220VAC

### Applications:

- Architectural Decorative Lighting
- Archway, Canopy & Bridge Edge Lighting
- Amusement Park, Theater & Aircraft Cabin Mood Lighting
- Emergency Hallway Lighting
- Auditorium Walkway Lighting
- Stairway Accent Lighting
- Concealed Lighting
- Backlighting for Sign Letters
- Channel Letter lighting
- Cove Lighting
- Landscape Lighting

- \* EASY INSTALLATION - NO LED DRIVER REQUIRED
- \* HIGH BRIGHTNESS & ENERGY EFFICIENT
- \* ENDLESS RESIDENTIAL & COMMERCIAL APPLICATIONS

