Light Source Specification



UFO MicroLED 4000 Light Source



The UFO MicroLED 4000 light source is a powerful, yet efficient fibre optic light source, powered by LED technology and controlled by an advanced RF remote control which features a multi-colour touch wheel allowing you to instantly switch to almost any colour imaginable.

The light source remote control also gives the ability to start and stop colour cycling on any colour. It is also features in-built synchronisation with the ability to control more than one unit with the same remote control.

Suitable for use in multiple applications, including:

- Sensory harnesses & systems
- Colour change downlight systems
- Colour change sparkle ceilings
- Fibre optic sideglow illumination

Description	
Port connector size	30mm diameter
Fibre type	Glass/Polymer
Max no. of fibre tails	900 x 0.75mm
Supply voltage	110VAC 60Hz / 230 VAC 50 Hz
Power supply	External 12V PSU
Power consumption	2-5W in colour cycle mode
Min. ambient temperature	-10°C
Max. ambient temperature	45°C
Operating environment	Indoor / dry
Material	Aluminium
Colour	Anodised silver
Size	106mm (L) x 94mm (W) x 68mm (H)

Like all our range, this light source is undergoing constant improvements and upgrades, so we reserve the right to alter specifications as required. UL approval for this model is currently being processed.



RF remote control unit which eliminates the need for an Infra-red eye.

Universal Fibre Optics Home Place, Coldstream, TD12 4DT, United Kingdom

Tel : +44 (0)1890 883416 | Fax: +44 (0)1890 883062 www.fibreopticlighting.com | info@fibreopticlighting.com